

View Online at <https://aerobasegroup.com/nsn/5306-00-924-1724>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.073 inches and 1.113 inches

Fastener Length:

Between 2.178 inches and 2.198 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.062 inches

Shank Unthreaded Hole Diameter:

0.065 inches first hole and 0.072 inches first hole

First Diameter From Head:

Between 0.248 inches and 0.249 inches

Second Diameter From Head:

Between 0.222 inches and 0.232 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.350 inches and 0.370 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.715 inches and 0.755 inches

Thread Diameter:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Hole Configuration Style:

Hexagon longitudinal hole

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.068 inches first hole and 2.088 inches first hole

Externally Relieved Body Diameter Quantity:

2

Material:

Steel

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0