## NSN 5306-00-925-4835

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-925-4835 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.500 inches and 0.578 inches **Fastener Length:** Between 0.578 inches and 0.625 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.204 inches Width Between Flats: Between 0.490 inches and 0.502 inches **Hole Diameter:** 0.070 inches **Grip Diameter:** Between 0.3112 inches and 0.3117 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.046 inches and 0.078 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Hexagon flats **Surface Finish:** 63.0 microinches grip Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment:** 

ouriace freatmen

**Passivate** 

## NSN 5306-00-925-4835

Close Tolerance Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization: Yes - demil/mli

Mil-std (military Standard):

Mil-s-18732 spec.