## NSN 5306-00-925-9697

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-925-9697

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

0.579 inches

#### Fastener Length:

1.599 inches

#### **Head Style:**

Double hexagon w/hole

**Head Height:** 

0.348 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

#### **Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

#### **Extended Washer Thickness:**

0.082 inches

#### Grip Diameter:

Between 0.3110 inches and 0.3120 inches

#### **Thread Diameter:**

0.312 inches

#### Grip Length:

1.000 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

180000 pounds per square inch

#### Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

## Material:

Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel comp 4140

## Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military

specification 3rd material response or mil-s-5626 military specification 4th material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

### Thread Series Designator:

Unf

#### Shelf Life:

N/a

# NSN 5306-00-925-9697

Shear Bolt - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

