

View Online at <https://aerobasegroup.com/nsn/5306-00-926-5600>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.687 inches and 0.813 inches

**Fastener Length:**

Between 2.437 inches and 2.563 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.150 inches and 0.163 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**Locking Feature:**

Patch threads or strip threads

**Shank Unthreaded Hole Diameter:**

0.109 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.687 inches and 1.813 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.312 inches first hole

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316

**Material Specification:**

Qq-s-763 federal specification all material responses or qq-w-423 federal specification all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-171 finish no.5.4 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-std-171 spec.