

View Online at <https://aerobasegroup.com/nsn/5306-00-926-5600>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.687 inches and 0.813 inches

Fastener Length:

Between 2.437 inches and 2.563 inches

Head Style:

Hexagon

Head Height:

Between 0.150 inches and 0.163 inches

Width Between Flats:

Between 0.428 inches and 0.438 inches

Locking Feature:

Patch threads or strip threads

Shank Unthreaded Hole Diameter:

0.109 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 1.687 inches and 1.813 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.312 inches first hole

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316

Material Specification:

Qq-s-763 federal specification all material responses or qq-w-423 federal specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171 finish no.5.4 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.