

View Online at <https://aerobasegroup.com/nsn/5306-00-926-5633>

Thread Direction:

Right-hand

Thread Length:

0.410 inches

Fastener Length:

Between 2.690 inches and 2.700 inches

Head Style:

Dee

Head Diameter:

Between 0.705 inches and 0.709 inches

Head Height:

0.200 inches

Distance From Centerline To Flat:

Between 0.293 inches and 0.298 inches

First Diameter From Head:

Between 0.402 inches and 0.406 inches

Second Diameter From Head:

0.472 inches

Third Diameter From Head:

Between 0.402 inches and 0.406 inches

Fourth Diameter From Head:

0.472 inches

Fifth Diameter From Head:

Between 0.402 inches and 0.406 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.160 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.430 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

1.110 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

1.190 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

1.790 inches

Thread Diameter:

0.469 inches

Nonstandard Thread Pitch Diameter:

+0.4370/+0.4385 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

Externally Relieved Body Diameter Quantity:

5

Special Features:

Sixth diameter from head 0.4720 in. Min diameter to 0.4724 in. Maximum diameter and located 2.170 in. From the bearing surface

Material:

Iron alloy 660

Material Specification:

Ams 5735 assn standard single material response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0