## NSN 5306-00-926-5680

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-926-5680



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.611 inches and 0.687 inches Fastener Length: Between 4.813 inches and 4.859 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: 0.070 inches **Thread Diameter:** 0.375 inches Grip Length: Between 4.172 inches and 4.202 inches **Hole Quantity:** 1 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 3135 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

## **Thread Series Designator:**

Unf

## NSN 5306-00-926-5680

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

