## NSN 5306-00-926-5680

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-926-5680

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.611 inches and 0.687 inches
Fastener Length:
Between 4.813 inches and 4.859 inches
Head Style:
Hexagon
Head Height:
Between 0.203 inches and 0.235 inches
Width Between Flats:
Between 0.553 inches and 0.565 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 4.172 inches and 4.202 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 3135
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:

Unf

## NSN 5306-00-926-5680

Machine Bolt - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0