

View Online at <https://aerobasegroup.com/nsn/5306-00-927-3564>

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Fastener Length:**

3.380 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.145 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**First Diameter From Head:**

Between 0.262 inches and 0.268 inches

**Second Diameter From Head:**

Between 0.307 inches and 0.309 inches

**Third Diameter From Head:**

Between 0.262 inches and 0.268 inches

**Fourth Diameter From Head:**

Between 0.307 inches and 0.309 inches

**Fifth Diameter From Head:**

Between 0.262 inches and 0.268 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.120 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.400 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.380 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

1.630 inches

**Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:**

2.880 inches

**Thread Diameter:**

0.312 inches

**Nonstandard Thread Pitch Diameter:**

+0.2874/+0.2898 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

79.0 rockwell superficial 15-n and 83.0 rockwell superficial 15-n

**Externally Relieved Body Diameter Quantity:**

5

**Material:**

Stainless steel

**Material Specification:**

-3603 91547 mfr ref single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0