

View Online at <https://aerobasegroup.com/nsn/5306-00-927-3564>

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

3.380 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.145 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

First Diameter From Head:

Between 0.262 inches and 0.268 inches

Second Diameter From Head:

Between 0.307 inches and 0.309 inches

Third Diameter From Head:

Between 0.262 inches and 0.268 inches

Fourth Diameter From Head:

Between 0.307 inches and 0.309 inches

Fifth Diameter From Head:

Between 0.262 inches and 0.268 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.120 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.400 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

1.380 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

1.630 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

2.880 inches

Thread Diameter:

0.312 inches

Nonstandard Thread Pitch Diameter:

+0.2874/+0.2898 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

79.0 rockwell superficial 15-n and 83.0 rockwell superficial 15-n

Externally Relieved Body Diameter Quantity:

5

Material:

Stainless steel

Material Specification:

-3603 91547 mfr ref single material response

Precious Material:

Silver

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0