

View Online at <https://aerobasegroup.com/nsn/5306-00-928-0513>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.134 inches and 1.154 inches

**Fastener Length:**

Between 3.355 inches and 3.375 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.240 inches and 0.260 inches

**Width Between Flats:**

Between 1.418 inches and 1.438 inches

**Shank Unthreaded Hole Diameter:**

0.156 inches first hole and 0.166 inches first hole

**First Diameter From Head:**

Between 0.989 inches and 0.999 inches

**Second Diameter From Head:**

Between 0.758 inches and 0.778 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 1.980 inches and 2.000 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 2.211 inches and 2.231 inches

**Thread Diameter:**

0.875 inches

**Thready Qty Per Inch (tpi):**

14

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.761 inches first hole and 2.781 inches first hole

**Externally Relieved Body Diameter Quantity:**

2

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

P.S.13001 fscm 76301 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0