

View Online at <https://aerobasegroup.com/nsn/5306-00-928-0513>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.134 inches and 1.154 inches

Fastener Length:

Between 3.355 inches and 3.375 inches

Head Style:

Hexagon

Head Height:

Between 0.240 inches and 0.260 inches

Width Between Flats:

Between 1.418 inches and 1.438 inches

Shank Unthreaded Hole Diameter:

0.156 inches first hole and 0.166 inches first hole

First Diameter From Head:

Between 0.989 inches and 0.999 inches

Second Diameter From Head:

Between 0.758 inches and 0.778 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 1.980 inches and 2.000 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 2.211 inches and 2.231 inches

Thread Diameter:

0.875 inches

Thready Qty Per Inch (tpi):

14

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.761 inches first hole and 2.781 inches first hole

Externally Relieved Body Diameter Quantity:

2

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

P.S.13001 fscm 76301 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0