NSN 5306-00-928-2358

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-928-2358 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.586 inches and 0.636 inches **Fastener Length:** Between 1.221 inches and 1.251 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.319 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** 0.050 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837, type 1 cl 2 military specification single treatment response or mil-c-8837, type 2 cl 2 military specification single treatment response

Unjf

Shelf Life:

Thread Series Designator:

N/a

NSN 5306-00-928-2358

Shear Bolt - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.