## NSN 5306-00-928-2360

Close Tolerance Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-928-2360



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.609 inches and 0.688 inches Fastener Length: Between 0.937 inches and 0.984 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.556 inches Hole Diameter: 0.070 inches **Grip Diameter:** Between 0.3737 inches and 0.3742 inches **Thread Diameter:** 0.375 inches Grip Length: Between 0.296 inches and 0.328 inches **Hole Quantity:** 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Surface Finish: 63.0 microinches grip Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 Surface Treatment: Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

## NSN 5306-00-928-2360

Close Tolerance Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

