## NSN 5306-00-928-2427

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-928-2427 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.063 inches and 1.141 inches **Fastener Length:** Between 6.766 inches and 6.812 inches **Head Style:** Hexagon **Head Height:** Between 0.390 inches and 0.422 inches Width Between Flats: Between 1.053 inches and 1.066 inches **Thread Diameter:** 0.750 inches **Grip Length:** Between 5.672 inches and 5.703 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 62000 pounds per square inch Material: Aluminum alloy **Material Specification:** Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Oxide film and anodize **Surface Treatment Specification:** Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A003b0

## NSN 5306-00-928-2427

Machine Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-c-5541 spec.