## NSN 5306-00-928-2529

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-928-2529

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.412 inches

#### Fastener Length:

0.912 inches

#### Head Style:

Double hexagon w/hole

**Head Height:** 

0.300 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

#### **Extended Washer Diameter:**

0.433 inches

#### **Extended Washer Thickness:**

0.069 inches

#### **Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

## **Thread Diameter:**

0.250 inches

## Grip Length:

0.500 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

#### Material:

Steel comp h11

#### Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Nas 672 assn standard single treatment response

## Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-00-928-2529

Shear Bolt - Page 2 of 2



---

Demilitarization:

No

Fiig:

A003b0

