NSN 5306-00-929-6230



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-929-6230 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.544 inches **Fastener Length:** 1.825 inches **Head Style:** Hexagon **Head Height:** 0.219 inches Width Between Flats: 1.000 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole and 0.151 inches first hole **Thread Diameter:** 0.625 inches **Grip Length:** 1.281 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.687 inches first hole **Product Name:** Navy special project Material: Steel comp e4340 **Material Specification:** Mil-s-5000 military specification single material response **Surface Treatment:** Mac p.S.-13145 fscm 76301 mfr ref single treatment response

Cadmium **Surface Treatment Specification: Thread Series Designator:** Unf Shelf Life: N/a

NSN 5306-00-929-6230

Machine Bolt - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.