NSN 5306-00-930-1200

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-930-1200 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: Between 0.645 inches and 0.685 inches **Fastener Length:** Between 3.210 inches and 3.230 inches **Head Style:** Hexagon **Head Height:** Between 0.209 inches and 0.229 inches Width Between Flats: Between 0.553 inches and 0.564 inches **First Diameter From Head:** 0.375 inches **Second Diameter From Head:** Between 0.315 inches and 0.325 inches Third Diameter From Head: Between 0.383 inches and 0.384 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.540 inches and 0.560 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 2.030 inches and 2.050 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 2.545 inches and 2.565 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 3 **Product Name:** Navy special project Material: Stainless steel **Material Specification:**

Ams 5616 assn standard single material response **Thread Series Designator:**

Unf

NSN 5306-00-930-1200

Externally Relieved Body Bolt - Page 2 of 2



\sim				
•	no	ıŦ	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0