

View Online at <https://aerobasegroup.com/nsn/5306-00-930-8965>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.404 inches and 0.414 inches

Fastener Length:

Between 4.780 inches and 4.800 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.365 inches and 0.385 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

Shoulder Diameter:

0.3745 inches first shoulder and 0.3755 inches first shoulder

Shoulder Length:

4.376 inches first shoulder and 4.386 inches first shoulder

Shank Unthreaded Hole Diameter:

0.065 inches first hole and 0.072 inches first hole

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.678 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0