

View Online at <https://aerobasegroup.com/nsn/5306-00-930-8966>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.388 inches

Fastener Length:

Between 1.581 inches and 1.602 inches

Head Style:

Round w/wrench flats

Head Diameter:

Between 0.615 inches and 0.635 inches

Head Height:

Between 0.115 inches and 0.135 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

First Diameter From Head:

Between 0.372 inches and 0.373 inches

Second Diameter From Head:

0.264 inches

Third Diameter From Head:

Between 0.190 inches and 0.200 inches

Fourth Diameter From Head:

0.264 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.191 inches and 0.192 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.371 inches and 0.402 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.971 inches and 1.002 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 1.131 inches and 1.152 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

35.0 rockwell c and 40.0 rockwell c

Externally Relieved Body Diameter Quantity:

4

Special Features:

Third diameter from head is 0.031-0.062r on ends; groove after fourth diameter from head is 0.185 porm 0.010 in. Dia

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0