NSN 5306-00-932-4170

Machine Bolt - Page 1 of 2

Between 1.365 inches and 1.385 inches

Thread Class:

Right-hand **Thread Length:**0.625 inches

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-00-932-4170

Double hexagon w/hole Head Height: Between 0.250 inches and 0.270 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
Between 0.250 inches and 0.270 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Between 0.365 inches and 0.385 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Between 0.040 inches and 0.050 inches Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Hole Diameter: 0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
0.045 inches Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Thread Diameter: 0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
0.190 inches Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Grip Length: Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Between 0.740 inches and 0.760 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating:
Thready Qty Per Inch (tpi): 32 Hardness Rating:
32 Hardness Rating:
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Material:
Steel
Material Specification:
Ams 5628 assn standard single material response
Surface Treatment:
Passivate

NSN 5306-00-932-4170

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0