NSN 5306-00-933-4583

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-933-4583

Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
Between 0.256 inches and 0.317 inches			
Fastener Length:			
Between 0.391 inches and 0.432 inches			
Head Style:			
Hexagon			
Head Height:			
Between 0.105 inches and 0.125 inches			
Width Between Flats:			
Between 0.365 inches and 0.377 inches			
Hole Diameter:			
0.046 inches			
Grip Diameter:			
Between 0.1885 inches and 0.1895 inches			
Thread Diameter:			
0.190 inches			
Grip Length:			
Between 0.115 inches and 0.135 inches			
Hole Quantity:			
3			
Hole Type:			
Drilled			
Thready Qty Per Inch (tpi):			
32			
Min. Tensile Strength (psi):			
180000 pounds per square inch			
Hardness Rating:			
39.0 rockwell c and 43.0 rockwell c			
Hole Configuration Style:			
Hexagon corners			
Material:			
Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740			
Surface Treatment:			
Cadmium and chromate			
Surface Treatment Specification:			
Qq-p-416, type 2, cl 2 federal specification single treatment response			
Thread Series Designator:			
Unjf			

NSN 5306-00-933-4583

Shear Bolt - Page 2 of 2



Spec	cific	ation	Data:
------	-------	-------	-------

76823-51b464-3a2h manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0