

View Online at <https://aerobasegroup.com/nsn/5306-00-933-4584>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.552 inches and 0.613 inches

**Fastener Length:**

Between 4.624 inches and 4.665 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.370 inches and 0.390 inches

**Width Between Flats:**

Between 1.052 inches and 1.065 inches

**Hole Diameter:**

0.070 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 4.052 inches and 4.072 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:**

Hexagon corners

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

76823-51b464 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0