NSN 5306-00-933-4584

Shear Bolt - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.552 inches and 0.613 inches Fastener Length: Between 4.624 inches and 4.665 inches **Head Style:** Hexagon **Head Height:** Between 0.370 inches and 0.390 inches Width Between Flats: Between 1.052 inches and 1.065 inches Hole Diameter: 0.070 inches **Grip Diameter:** Between 0.7480 inches and 0.7490 inches **Thread Diameter:** 0.750 inches Grip Length: Between 4.052 inches and 4.072 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Hole Configuration Style: Hexagon corners Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:**

Unjf

3

NSN 5306-00-933-4584

Shear Bolt - Page 2 of 2

Specification Data:

76823-51b464 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

