## NSN 5306-00-934-0174

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-934-0174

Thread Class
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.663 inches
Fastener Length:
2.351 inches
Head Style:
Hexagon
Head Height:
0.219 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole
Thread Diameter:
0.375 inches
Grip Length:
1.688 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
140000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
2.126 inches first hole
Material:
Iron alloy 660
Material Specification:
Ams5732 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas1006 professional/industrial association standard
Shelf Life:

N/a

## **NSN 5306-00-934-0174** Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

Demilitarization:

No

Fiig:

A003b0