

View Online at <https://aerobasegroup.com/nsn/5306-00-935-2990>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.285 inches

**Fastener Length:**

Between 1.910 inches and 1.950 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

0.875 inches

**Head Height:**

0.190 inches

**Width Between Flats:**

Between 0.740 inches and 0.750 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Concentric Hole Depth:**

Between 1.530 inches and 1.560 inches

**Concentric Hole Diameter:**

0.250 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.800 inches first hole

**Material:**

Steel comp 4340

**Surface Treatment:**

Cadmium head

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0