

View Online at <https://aerobasegroup.com/nsn/5306-00-935-3023>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.366 inches and 0.416 inches

**Fastener Length:**

Between 1.938 inches and 1.968 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.552 inches and 1.572 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1106 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0