

View Online at <https://aerobasegroup.com/nsn/5306-00-935-3041>

**Thread Direction:**

Right-hand

**Thread Length:**

0.225 inches

**Fastener Length:**

Between 1.290 inches and 1.310 inches

**Head Style:**

Hexagon

**Head Height:**

0.125 inches

**Width Between Flats:**

0.375 inches

**First Diameter From Head:**

Between 0.186 inches and 0.189 inches

**Second Diameter From Head:**

Between 0.140 inches and 0.145 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.480 inches and 0.500 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 1.050 inches and 1.065 inches

**Thread Diameter:**

0.190 inches

**Nonstandard Thread Pitch Diameter:**

+0.1643/+0.1667 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

29.0 rockwell c and 34.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Stainless steel

**Precious Material:**

Silver

**Surface Treatment:**

Silver threads

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response threads

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0