# NSN 5306-00-936-2429

Shear Bolt - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.444 inches and 0.504 inches

#### Fastener Length:

Between 3.579 inches and 3.619 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.156 inches and 0.171 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.3110 inches and 0.3120 inches

#### **Thread Diameter:**

0.312 inches

# Grip Length:

Between 3.115 inches and 3.135 inches

# Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

#### Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

#### Thread Series Designator:

Unf

#### **Specification Data:**

80205-nas1305 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5306-00-936-2429

Shear Bolt - Page 2 of 2

Fiig: A003b0

