# NSN 5306-00-936-9560

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-936-9560



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

Between 0.401 inches and 0.421 inches

#### Fastener Length:

0.500 inches

#### **Head Style:**

Double hexagon w/hole

**Head Height:** 

0.330 inches

Width Between Flats:

Between 0.305 inches and 0.313 inches

#### **Extended Washer Diameter:**

0.438 inches

#### **Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

#### Hole Diameter:

0.070 inches

### **Thread Diameter:**

0.250 inches

## Grip Length:

Between 0.079 inches and 0.099 inches

#### Hole Quantity:

4

### Hole Type:

Drilled

#### **Features Provided:**

Finished head

### Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

195000 pounds per square inch

## Hardness Rating:

42.0 rockwell c and 46.0 rockwell c

# Hole Configuration Style:

Double hexagon longitudinal hole

# Surface Finish:

32.0 microinches threads

## Material:

Steel comp 601

# NSN 5306-00-936-9560

Machine Bolt - Page 2 of 2



Material Specification: Ams 6304 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0