NSN 5306-00-937-2295

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-937-2295 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.890 inches **Fastener Length:** 2.650 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** 0.875 inches **Extended Washer Thickness:** 0.140 inches **First Diameter From Head:** Between 0.460 inches and 0.470 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.760 inches **Thread Diameter:** 0.562 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 18 Hardness Rating: 32.0 rockwell c and 37.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8640 or steel comp 8637 or steel comp 4140 **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232 type m, class 2 military specification single treatment response

Unf

Thread Series Designator:

NSN 5306-00-937-2295

Externally Relieved Body Bolt - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
NO
Fiig:

Mil-std (military Standard): Mil-p-16232 spec.