NSN 5306-00-938-3228

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-938-3228 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.877 inches and 1.027 inches **Fastener Length:** Between 8.824 inches and 8.954 inches **Head Style:** Dished hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 7.927 inches and 7.947 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1310 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5306-00-938-3228

Shear Bolt - Page 2 of 2



Fiig:

A003b0