

View Online at <https://aerobasegroup.com/nsn/5306-00-938-9229>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.701 inches and 0.748 inches

**Fastener Length:**

Between 2.701 inches and 2.748 inches

**Head Style:**

Double hexagon

**Head Height:**

0.350 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

2.000 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

156000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.582 inches first hole and 2.614 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel

**Material Specification:**

H-11, stsbs001, lockheed aircraft corporation mfr ref single material response

**Surface Treatment:**

Nickel and cadmium and chromium

**Surface Treatment Specification:**

Stsb001 fscm 98897 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0