

View Online at <https://aerobasegroup.com/nsn/5306-00-938-9229>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.701 inches and 0.748 inches

Fastener Length:

Between 2.701 inches and 2.748 inches

Head Style:

Double hexagon

Head Height:

0.350 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

2.000 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

156000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.582 inches first hole and 2.614 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel

Material Specification:

H-11, stsbs001, lockheed aircraft corporation mfr ref single material response

Surface Treatment:

Nickel and cadmium and chromium

Surface Treatment Specification:

Stsb001 fscm 98897 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0