NSN 5306-00-939-0694

Shoulder Bolt - Page 1 of 2



| Shoulder Boil - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5306-00-939-0694 |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.500 inches |
| Fastener Length: |
| 1.250 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.250 inches |
| Width Between Flats: |
| Between 0.492 inches and 0.502 inches |
| Extended Washer Diameter: |
| 0.680 inches |
| Extended Washer Thickness: |
| 0.030 inches |
| Shoulder Diameter: |
| 0.311 inches first shoulder and 0.313 inches first shoulder |
| Shoulder Length: |
| 0.600 inches first shoulder |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hardness Rating: |
| 34.0 rockwell c and 40.0 rockwell c |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-7108 military specification single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2 cl 3 federal specification single treatment response |
| Thread Series Designator: |
| llof |

Unf

NSN 5306-00-939-0694

Shoulder Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7108 spec.

