

View Online at <https://aerobasegroup.com/nsn/5306-00-939-9723>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.569 inches and 0.660 inches

**Fastener Length:**

Between 0.640 inches and 0.660 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Hole Diameter:**

0.068 inches

**Shank Unthreaded Hole Diameter:**

0.060 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.535 inches first hole and 0.545 inches first hole

**Surface Finish:**

63.0 microinches bearing surface of head

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0