## NSN 5306-00-941-0133

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-941-0133 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.237 inches and 0.247 inches **Fastener Length:** Between 2.770 inches and 2.790 inches **Head Style:** Hexagon **Head Height:** Between 0.271 inches and 0.291 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Shoulder Diameter:** 0.506 inches **Shoulder Length:** Between 2.405 inches and 2.409 inches **Shank Unthreaded Hole Diameter:** 0.094 inches first hole and 0.101 inches first hole **Concentric Hole Depth:** Between 2.330 inches and 2.350 inches **Concentric Hole Diameter:** Between 0.050 inches and 0.070 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 2.642 inches first hole and 2.656 inches first hole Material: Stainless steel **Material Specification:** Ams 5616 assn standard single material response **Style Designator:** Concentric hole unthreaded **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-00-941-0133

Internally Relieved Body Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0