NSN 5306-00-941-3772

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-941-3772 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.800 inches and 0.820 inches **Fastener Length:** Between 1.740 inches and 1.760 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.158 inches and 0.178 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** 0.062 inches **First Diameter From Head:** Between 0.221 inches and 0.231 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.940 inches and 1.000 inches **Thread Diameter:** 0.250 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Round longitudinal hole **Externally Relieved Body Diameter Quantity:** 1 Material:

Steel comp 8740

Material Specification:

Ams 6322 assn standard single material response

NSN 5306-00-941-3772

Externally Relieved Body Bolt - Page 2 of 2



Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams 2400 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A003b0