

View Online at <https://aerobasegroup.com/nsn/5306-00-942-2199>

Thread Direction:

Right-hand

Thread Length:

Between 0.625 inches and 0.685 inches

Fastener Length:

1.625 inches

Head Style:

Double hexagon w/hole

Head Height:

0.260 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

0.375 inches

Extended Washer Thickness:

Between 0.040 inches and 0.050 inches

Hole Diameter:

0.047 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.940 inches and 1.000 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Nonstandard Thread Pitch Diameter:

+0.1644/+0.1667 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

63.0 microinches grip

Material:

Iron alloy 660

Material Specification:

Ams5732 assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0