NSN 5306-00-942-2568

View Online at https://aerobasegroup.com/nsn/5306-00-942-2568

Shoulder Bolt - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.400 inches **Fastener Length:** Between 0.640 inches and 0.660 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Shoulder Diameter:** 0.247 inches first shoulder and 0.248 inches first shoulder **Shoulder Length:** 0.260 inches first shoulder and 0.280 inches first shoulder **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** Ams 6922 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5306-00-942-2568 Shoulder Bolt - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

Demilitarization:

No

Fiig:

A003b0