

View Online at <https://aerobasegroup.com/nsn/5306-00-942-5335>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.406 inches and 0.431 inches

**Fastener Length:**

Between 1.040 inches and 1.060 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.080 inches

**Shoulder Diameter:**

0.247 inches first shoulder and 0.248 inches first shoulder

**Shoulder Length:**

0.631 inches first shoulder and 0.634 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.065 inches first hole and 0.072 inches first hole

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

35.0 rockwell c and 40.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.910 inches first hole and 0.930 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Stainless steel

**Material Specification:**

Ams 5616 assn standard single material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

Ams 2406 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0