## NSN 5306-00-943-2413



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-943-2413 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.450 inches and 0.490 inches **Fastener Length:** Between 2.350 inches and 2.370 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Shank Unthreaded Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.880 inches and 1.900 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 35.0 rockwell c and 40.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 2.240 inches first hole and 2.260 inches first hole **Surface Finish:** 63.0 microinches grip Material: Stainless steel

**Material Specification:** 

Ams 5616 assn standard single material response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## **NSN 5306-00-943-2413** Machine Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A003b0