## NSN 5306-00-943-6927

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-943-6927

## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.469 inches

#### Fastener Length:

2.219 inches

#### Head Style:

Dished hexagon

#### **Head Height:**

0.156 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Hole Diameter:

0.070 inches

## Grip Diameter:

Between 0.3110 inches and 0.3120 inches

#### Thread Diameter:

0.312 inches

#### Grip Length:

1.750 inches

#### Hole Quantity:

3

## Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

## Hole Configuration Style:

Hexagon corners

## Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

## Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

# NSN 5306-00-943-6927

Shear Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.

