NSN 5306-00-944-2637



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-944-2637 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.376 inches and 0.438 inches **Fastener Length:** 0.438 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Hole Diameter:** 0.047 inches **Thread Diameter:** 0.190 inches **Hole Quantity: Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

63.0 microinches grip

Material:

Iron alloy 660

NSN 5306-00-944-2637

Machine Bolt - Page 2 of 2



N	later	וכוי	~n	α CIT	1021	ınn.

Ams 5732 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0