

View Online at <https://aerobasegroup.com/nsn/5306-00-945-8601>

Thread Direction:

Right-hand

Thread Length:

Between 0.471 inches and 0.552 inches

Fastener Length:

Between 0.552 inches and 0.575 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.060 inches

Thread Diameter:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Unfinished head

Nonstandard Thread Pitch Diameter:

+0.2213/+0.2238 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

150000 pounds per square inch

Minimum Yield Strength:

100000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

63.0 microinches bearing surface of head

Material:

Stainless steel

Material Specification:

Ams 7477 assn standard single material response

Precious Material:

Silver

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0