NSN 5306-00-945-8604

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-945-8604 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.413 inches **Fastener Length:** Between 0.595 inches and 0.615 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** 0.062 inches First Diameter From Head: Between 0.261 inches and 0.265 inches **Second Diameter From Head:** Between 0.197 inches and 0.201 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.110 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.162 inches and 0.202 inches **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Round longitudinal hole **Externally Relieved Body Diameter Quantity:**

Product Name:

Navy special project

NSN 5306-00-945-8604

Externally Relieved Body Bolt - Page 2 of 2



Material:
Iron alloy 660
Material Specification:
Ams 5735 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0