## NSN 5306-00-947-4249

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-947-4249 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.658 inches and 0.678 inches **Fastener Length:** 0.750 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Hole Diameter:** 0.047 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.072 inches and 0.092 inches **Hole Quantity:** 4 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 195000 pounds per square inch **Hardness Rating:** 42.0 rockwell c and 46.0 rockwell c **Hole Configuration Style:** Hexagon longitudinal hole **Surface Finish:** 

32.0 microinches threads

Material:

Steel comp 601

## **NSN 5306-00-947-4249** Machine Bolt - Page 2 of 2

No Fiig: A003b0



Material Specification:
Ams 6304 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams 2416 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: