## NSN 5306-00-948-0661

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-948-0661
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.840 inches
Fastener Length:
5.590 inches
Head Style:
Dished hexagon
Head Height:
0.281 inches
Width Between Flats:
Between 0.865 inches and 0.877 inches
Grip Diameter:
Between 0.5605 inches and 0.5615 inches
Thread Diameter:
0.562 inches
Grip Length:
4.750 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas1309 professional/industrial association standard
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5306-00-948-0661

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.