NSN 5306-00-948-4188

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-948-4188

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.468 inches |
| Fastener Length: |
| 5.156 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.140 inches and 0.172 inches |
| Width Between Flats: |
| Between 0.428 inches and 0.440 inches |
| Hole Diameter: |
| 0.046 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 4.688 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 62000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Aluminum alloy 2024 or aluminum alloy |
| Material Specification: |
| Qq-a-267 federal specification 1st material response or qq-a-268 federal specification 1st material response or mil-w-7986 military |
| specification 2nd material response |
| Surface Treatment: |
| Oxide film and anodize |
| |

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response

Thread Series Designator:

NSN 5306-00-948-4188

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-w-7986 spec.

