## NSN 5306-00-948-4433

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-948-4433 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.926 inches and 0.966 inches **Fastener Length:** 2.622 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.557 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** 0.133 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Thread Diameter:** 0.562 inches **Grip Length:** 1.565 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches grip Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** 

N/a

Shelf Life:

Unf

## NSN 5306-00-948-4433

Close Tolerance Bolt - Page 2 of 2



 :4	$\sim$	Measure:
 nit	l IT	MESCITE.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.